


Elmo Rietschle V-Series

Oil-free rotary vane air compressors for low pressure applications up to 14.5 psig



V-DTE 3/6/8/10

V-DTE 3, 6, 8, 10

Avantages

- Compact design.
- Easy to install.
- Corrosion-proof rotors.
- Hose connection & exhaust silencer as standard.

Features

- Volume flow 3.5 to 12 m³/hr
- Volume flow 2.1 to 7.1 cfm
- Pressure up to 1 bar



V-DTA 50/60/80/100/140

V-DTA 50, 60, 80, 100, 140

Avantages

- Bearings on both sides of the rotor.
- High efficiency.
- Low noise level.
- Sound cover allows a ducted cooling air outlet either from one side only or from both sides.
- Easy servicing and operation.

Features

- Volume flow 34.1 to 51.7 cfm
- Pressure up to 1.5 bar for continuous operation and 2.2 bar for intermittent operation



V-DTR 100/140

V-DTR 100, 140

Avantages

- Bearings on both sides of the rotor.
- Flange motor with torsionally flexible coupling.
- High efficiency.
- Silent operation.
- Sound cover allows a ducted cooling air outlet.
- Easy servicing and operation.

Features

- Volume flow 100 to 153 m³/hr
- Volume flow 58.8 to 90 cfm
- Pressure up to 1.5 bar for continuous operation and up to 2.2 bar for intermittent operation

Spec sheet

• Elmo Rietschle V-DTE 3/6/8/10

[Download](#)

• Elmo Rietschle V-DTR 100/140

[Download](#)

• Elmo Rietschle V-DTA 50/60/80/100/140

[Download](#)